

Typ A15

100% PTFE tape packing with cover braid and additional outside PTFE tape wrap



Main areas of application:




- Fittings
- Valves
- Mixers
- Tank- and lid seals

Characteristics:

- Low coefficient of friction
- Good adaption to any kind of surface
- Not ageing or hardening
- Used as spiral guarantees simple assembly and disassembly in one piece

Suitable for:

- Chemical and universal plant service application

			
p [bar]	20	20	100
v [m/s]	1	1	-
t °C	-200 ... +280 (200*)		
pH	0 - 14		
g/cm ³	1.45		

*practically useful data

Form of delivery:

This packing can be manufactured from 2 to 30 mm diameter. Other lengths and dimensions on request.

All dimensions will be shipped in meters on rolls.

* Available meter length for order specifications:

[size]	2	4	6	8	10	12	16	18	20
[m*]	25/50	10/50	7,5/50	5/30	5/30	5/30	5/20	5/20	5/20

All technical information and advice is based on our experience and will be given most conscientiously but without any liability. Indication and figures need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.

**ProPack Dichtungen
und Packungen AG**
Rudolf-Diesel-Ring 28
D-82054 Sauerlach
Germany

Telefon: +49 8104 6640-0
Telefax: +49 8104 6640-44
Email: propack@propack.ag
Internet: <http://www.propack.ag>

Distributed by:

Our Purpose: 'To give our customers such exceptional service that they need never consider alternative sources of supply.'