




Style A19 "Spezial"

100% PTFE-fibre with special PTFE dispersion



			
p [bar]	25	250	500
v [m/s]	2	1.5	-
t °C	-200 ... +280		
pH	0 - 14		
g/cm ³	1.6		

Main areas of application:

- Armatures
- Valves
- Gate valves
- Slow running shafts
- Piston pumps
- Door & lid seals

Characteristics:

- In high pressure and vacuum applications die formed rings are recommended
- Extreme long operational period, no wear
- Once installed very little maintenance effort in operation necessary

Suitable for:

- Plant wide use, chemical, pulp and paper industry, generally in strong and concentrated chemicals

Approvals:

- A special style A190X has FDA conformity as well as BAM approval for the use in oxygen at 60° / 30 bar, certificate on request

Form of delivery:

This packing can be manufactured from 3 to 40 mm square as well as in intermediate, inch sizes and special dimension.

04 - 09 mm	on	1 kg spool	Special length, pre-cut or die formed rings on request.
10 - 15 mm	on	2.5 kg spool	
16 mm and above	on	5 kg spool	

1 kg of packing of the following cross-sections corresponds to displayed metre lengths:

[size]	04	05	06	1/4"	08	3/8"	10	12	1/2"	14	15	16	18	19	20	22	25
[m]	39	25	17,4	15,5	9,8	6,9	6,3	4,34	3,88	3,19	2,78	2,44	1,9	1,73	1,56	1,3	1

All technical information and advice is based on our experience and will be given most conscientiously but without any liability. Indication and figures need to be examined by the user. All sizes are subject to manufacturing tolerances. We reserve the right to modify specifications at any time.